

# TS-15R



► FEATURES

- **Elegant and slim dual tone design**
- **Sharp 500 contrast ratio**
- **High 400 brightness for more vibrant and colorful images**
- **Speedy 5-wire Resistive touch technology**
- **Suitable for use with such input devices as a pen, stylus, or gloved hand**
- **35 million touch stability**
- **Auto-adjustment for optimal setting**
- **User-friendly OSD with lockable key function**
- **Kensington® security slot**
- **VESA compliant for easy wall or arm configuration**



► SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD
	<b>Panel Size</b>	15.0" (381mm)
	<b>Max. Resolution</b>	XGA 1024 x 768
	<b>Pixel Pitch</b>	0.267mm
	<b>Brightness</b>	400cd/m <sup>2</sup> (Typical)
	<b>Contrast Ratio</b>	500:1 (Typical)
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment
	<b>Viewing Angle (H/V)</b>	130°/110° (Typical)
	<b>Display Color</b>	16.7M
	<b>Response Time</b>	16ms (GTG)
Input	<b>Frequency (H/V)</b>	H: 30kHz - 60kHz V: 50Hz - 75Hz
	<b>Max. Pixel Clock</b>	80MHz
Connector	<b>Life Time</b>	50,000hrs (Minimum)
	<b>Touch Interface</b>	8-Pin Mini Dim
Touch Screen	<b>Analog</b>	15-Pin D-Sub
	<b>Power</b>	3-Pin AC Plug
Technology	<b>Technology</b>	Resistive (5-Wire)
	<b>Optical Transmission</b>	>82% +/- 2%
	<b>Positional Accuracy</b>	<1% within precision area
	<b>Panel Resolution</b>	16K x 16K
	<b>Active Force</b>	25g - 50g
	<b>Panel Interface</b>	RS-232
	<b>Glass Thickness</b>	0.14mm
	<b>Life Performance</b>	35 million touches at a single point
	<b>Operational Temp.</b>	-20°C to 50°C
	<b>Storage Temp.</b>	-40°C to 70°C
Humidity	<b>Humidity</b>	90% RH from + 50°C 20~50%RH from -20°C to +50°C
	<b>Tilt</b>	+10°
Mounting	<b>VESA FPMPI</b>	Yes (75mm)
Regulation Approval	<b>Safety &amp; EMI</b>	UL/CUL, TUV/GS, NORDIC, CB, TCO 99, FCC, CE, EPA, ISO 13406-2
	<b>VESA</b>	DDC 1/2B, DPMS
Power	<b>Power AC</b>	100 - 240V, 50 - 60Hz
	<b>Consumption</b>	<40W (On) <4W (Stand-by) <2W (Off)
	<b>Dimensions</b>	<b>Net (W x H x D)</b> 386 x 360 x 169mm (15.1" x 14.2" x 6.7") <b>Packing (W x H x D)</b> 480 x 485 x 210mm (18.9" x 19.1" x 8.3")
Weight	<b>Net Weight</b>	4.6Kg (10.1lbs)
	<b>Gross Weight</b>	6.6Kg (14.5lbs)
Packing	<b>1 Pallet</b>	40 Cartons
	<b>20' Container</b>	480 Sets
	<b>40' Container</b>	960 Sets

All specifications are subject to change without prior notice