

# TS-17R



## ▶ FEATURES

- **Elegant and slim dual tone design**
- **Sharp 500 contrast ratio**
- **High 300 brightness for more vibrant and colorful images**
- **5-wire Resistive touch technology**
- **Scratch resistant touch panel**
- **35 million finger-touch hits and 100,000 characters input stability**
- **Auto-adjustment for optimal setting**
- **User-friendly OSD with lockable key function**
- **Kensington® security socket**
- **VESA compliant for easy wall or arm configuration**



## ▶ SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD
	<b>Panel Size</b>	17.0" (432mm)
	<b>Max. Resolution</b>	SXGA 1280 x 1024
	<b>Pixel Pitch</b>	0.264mm
	<b>Brightness</b>	300cd/m <sup>2</sup> (Typical)
	<b>Contrast Ratio</b>	500:1 (Typical)
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment
	<b>Viewing Angle (H/V)</b>	140°/130° (Typical)
	<b>Display Color</b>	16.7M
	<b>Response Time</b>	4ms (GTG)
Input	<b>Frequency (H/V)</b>	H: 31kHz – 82kHz V: 50Hz – 75Hz
	<b>Max. Pixel Clock</b>	135 MHz
Connector	<b>Life Time</b>	50,000hrs (Typical)
	<b>Touch Interface</b>	8-Pin Mini Dim
	<b>Analog</b>	15-Pin D-Sub
Touch Screen	<b>Digital</b>	29-Pin DVI-D
	<b>Power</b>	DC+12V
Screen	<b>Technology</b>	5-wire Resistive
	<b>Optical Transmission</b>	>80%
	<b>Positional Accuracy</b>	<1% within precision area
	<b>Active Force</b>	300 g
	<b>Panel Interface</b>	RS-232, available in TS-17R(RS-232) Or USB, available in TS-17R(USB)
	<b>Glass Thickness</b>	2.1mm
	<b>Life Performance</b>	35 million hits (finger) 100,000 characters input (pen)
	<b>Operational Temp.</b>	-20°C to 70°C
	<b>Storage Temp.</b>	-40°C to 80°C
	<b>Humidity</b>	Operating: <90%RH from -20°C to 60°C Operating: 133.8 g/m <sup>3</sup> , if >60°C Storage: <95%RH from -20°C to 60°C Storage: 142.9g/m <sup>3</sup> , if >60°C
Tilt	<b>Tilt</b>	+5°
Mounting	<b>VESA FPMPMI</b>	Yes (100mm)
Regulation Approval	<b>Certifications &amp; Compliance</b>	UL/CUL, TUV/ GS, CB, FCC, CE, WEEE, RoHS, EPA <b>VESA</b> DDC /CI, DPMS, DDC2B
Power	<b>Power AC</b>	100 - 240V, 50 - 60Hz
	<b>Consumption</b>	<35W (On) <2W (Stand-by) <1W (Off)
	<b>Dimensions</b>	<b>Net (W x H x D)</b> 436 X 427 X 200 mm (17.2" x 16.8" x 7.9") <b>Packing (W x H x D)</b> 525 x 550 x 175 mm (20.7" x 21.7" x 6.9")
Weight	<b>Net Weight</b>	7.5 Kg (16.52lbs)
	<b>Gross Weight</b>	10Kg (22 lb)
Packing	<b>1 Pallet</b>	36 Cartons
	<b>20' Container</b>	360 Sets
	<b>40' Container</b>	720 Sets

All specifications are subject to change without prior notice

[www.agneovo.com](http://www.agneovo.com)

Copyright © 2007 AG Neovo. All rights reserved.  
The name AG Neovo is a trademark of Associated Industries China, Inc.  
All other trademarks are the property of their respective owners.